

SMR-267

1K ACRYLIC SEALER Grey

TECHNICAL DATA

DESCRIPTION:

SMR-267 1K Acrylic Sealer is a ready-to-spray acrylic sealer with superior adhesion and excellent color holdout. This non-sanding sealer is designed for use under a wide variety of topcoats, while maintaining excellent DOI. SMR-267 is ideal for spot and panel applications and can be used on small bare steel, sand-thru areas.

PACKAGING:

Part Number	Description	Size	Qty. Case
SMR-267	1K ACRYLIC SEALER	Gallon	4

SURFACE PREPARATION

Wash area with soap and water, then thoroughly clean with wax and grease remover
Sand surface with 400 - 600 grit sandpaper
Re-clean area with wax and grease remover before applying SMR-267.

APPLICATION

- SHAKE or STIR well before each use.
- Apply 1 uniform coat using a good quality spray gun with a 1.3mm-1.4mm fluid tip. Allow 30 minutes before topcoating.

GUN SETUP

	Fluid Tip	psi
HVLP	1.3mm-1.4mm	8-10 psi
Conventional Gravity Feed	1.3mm-1.4mm	40-45 psi

DRY TIMES

Air Dry	
Topcoat	30 minutes

VOC INFORMATION

Coating Category: Primer Sealer

	Regulatory VOC	Regulatory VOC	Actual VOC	Actual VOC	Volatile Wt.	Water Wt.	Exempt	Density
	lbs/gal	g/l	lbs/gal	g/l	%	%	Compounds	g/l
SMR-267	4.58	549	2.17	260	73.67	0	46.8	8.09
RTS VOC		549						

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions.

- The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels and SDSs of all component, since the mixture will have the hazards of all its parts.
- Improper handling and use, for example, poor spray technique, inadequate engineering controls, and or lack of Personal Protective Equipment (PPE), may result in hazardous conditions or injury.
- Follow spray equipment manufacturer's instructions to prevent personal injury or fire.
- Provide adequate ventilation for health and fire hazard control.
- Follow company, product SDS and respirator manufacturer's recommendations for selection and proper use of respiratory protection. Be sure employees are adequately trained on the safe use of respirators per company and regulatory requirements.
- Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on MSDS.
- Always observe all applicable precautions and follow good safety and hygiene practice.